


America's Choice®



Anti-Wear Hydraulic Oils

America's Choice® Anti-Wear Hydraulic Oils contain a zinc/phosphorous additive to minimize wear in high speed, high-pressure vane, gear and piston pumps. Meets Cincinnati Machine P-68, P-69, P-70, Denison HF-0, HF-1, HF-2, Eaton/Vickers M-2950-S, I-286-S, Ford M6C32, Daimler Chrysler, General Motors LS-2 and US Steel 136 specifications for stability and durability.

Safety-Kleen's closed loop re-refining process takes used oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined oil. Re-refining oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

TYPICAL PROPERTIES

America's Choice®	22	32	46	68	100	150
Specific Gravity						
@ 15.6 °C865	.865	.868	.870	.874	.880
Viscosity						
cSt @ 40 °C	22.2	32.3	44.2	65.7	95.9	146.4
cSt @ 100 °C.....	4.4	5.5	6.8	8.9	11.4	14.8
Viscosity Index	106	109	109	109	106	102
Flash Point, °C.....	190	190	200	214	218	240
Pour Point, °C	-39	-36	-33	-30	-21	-15
Color (ASTM)	2.0	2.0	2.5	3.5	4.0	4.5
Oxidation, ASTM D943, HRS	3,000	3,000	3,000	2,000	1,500	1,500
Rust Protection, ASTM D665 A&B	Pass	Pass	Pass	Pass	Pass	Pass
Demulsibility, ASTM D1401	40/37/3(30)	40/37/3(30)	40/37/3(30)	40/37/3(30)	40/37/3(30)	40/37/3(30)
Copper Corrosion, ASTM D130	1A	1A	1A	1A	1A	1A

Note: The values shown are representative of current production and may vary within modest ranges.

Available in bulk



Safety-Kleen Systems, Inc.
safety-kleen.com, ac-rerefined.com

Customer Service 1-800-525-5739

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

