

# America's Choice®



## Motor Oil

**America's Choice®** Passenger Car Motor Oils are formulated for maximum performance with high quality additives and premium re-refined base oils. SAE 5W-20, 5W-30 and 10W-30 are energy conserving motor oils that exceed API service SM, SL, SJ, SH and ILSAC GF-1,GF-2, GF-3 and GF-4.

Safety-Kleen's closed loop re-refining process takes used motor oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined motor oil. Re-refining motor oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

### TYPICAL PROPERTIES

<i>America's Choice®</i>	SAE	5W-20	5W-30	10W-30
API Service .....		SM	SM	SM
Specific Gravity				
@ 15.6 °C .....		0.863	0.863	0.872
Viscosity				
cSt @ 40 °C .....		46	62	69
cSt @ 100 °C.....		8.3	10.5	10.7
Viscosity Index .....		155	160	145
CCS Viscosity				
cP @ -30 °C .....		3,700	6,200	NA
cP @ -25 °C .....		NA	NA	6,000
Flash Point, °C.....		200	200	210
Pour Point, °C .....		-39	-39	-36
Color (ASTM) .....		2.5	2.5	3
Sulfated Ash, wt % .....		0.85	0.85	0.85

*Note: The values shown are representative of current production and may vary within modest ranges.*

Available in bulk and quart bottles



Safety-Kleen Systems, Inc.  
safety-kleen.com, ac-rerefined.com

**Customer Service 1-800-525-5739**

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

