

America's Choice®



NGP Natural Gas Diesel Motor Oil

America's Choice® NGP Natural Gas Diesel Motor Oils are specially formulated to exceed the requirements of natural gas or propane fueled heavy-duty engines. Its low phosphorous content makes it compatible with catalytic converter equipped engines. It exceeds API quality levels and meets Cummins and Detroit Diesel specifications.

Safety-Kleen's closed loop re-refining process takes used motor oil and re-refines it into an exceptional quality base oil that is combined with premium additives to create a high performing re-refined motor oil. Re-refining motor oils is an infinitely better way to protect our environment and economy by reducing heavy metal emissions, greenhouse gases and our dependence on foreign oil.

Safety-Kleen, the world's leader in re-refining technology, re-refines **America's Choice®** base oils at our two state-of-the-art re-refineries in East Chicago, Indiana and Breslau, Ontario.

TYPICAL PROPERTIES

| <i>America's Choice®</i> | SAE | NGP 15W-40 | NGP-2 15W-40 |
|--------------------------------|-----|---------------|-----------------|
| Density, kg/m ³ | | | |
| @ 15 °C | | 876 | 876 |
| Viscosity, kinematic (D445) | | | |
| cSt @ 100 °C..... | | 15.5 | 15.5 |
| cSt @ 40 °C | | 135 | 135 |
| Viscosity Index | | 120 | 120 |
| CCS Viscosity (D5293) | | | |
| cP @ -15 °C | | 3,200 | 3,200 |
| Flash Point, °C..... | | 240 | 240 |
| Pour Point, °C | | -33 | -33 |
| TBN (D2896) | | 5.3 | 5.3 |
| TAN (D664) | | 0.6 | 0.6 |
| Sulfated Ash, %wt. | | 0.3 | 0.3 |
| Phosphorous Content, ppm | | 300 | 725 |
| Zinc Content, ppm | | 310 | 750 |
| Calcium Content, ppm | | 1,200 | 1,200 |

Note: The values shown are representative of current production and may vary within modest ranges.

Available in bulk



Safety-Kleen Systems, Inc.
safety-kleen.com, ac-rerefined.com

Customer Service 1-800-525-5739

5400 Legacy Drive, Cluster II, Building 3, Plano, TX 75024

